ALTERNATOR

| Frequency | 50 Hz |
|---------------------------------|-----------|
| Power | 1034 kVA |
| Voltage | 400 V |
| Nb of Phases | 3 |
| Aut. Voltage Regulator (AVR) | AS440 |
| Voltage Regulation | ±1% |
| Insulation Class | Н |
| Protection Standard | IP22-IP23 |
| Power Factor | 0.8 Cos |
| | |

ENGINE

- CUMMINS heavy duty diesel
- engine 12V / 24V starter and charge
- alternatör alternator Replaceable air, fuel and oil filters Mechanical governor control Tropical type radiator Flexible fuel hose
- -
- _
- Oil drain valve and extension höse Industrial type silencer and steel compensator Maintenance-free starter battery
- Water jacket heater 1500 rpm engine speed

DIMENSIONS & WEIGHT

WITH CANOPY: Weight (Kg): 9350 Length L(mm) Width W (mm) Height H (mm):6200x2200x2800 Fuel Tank Capacity (L): 1600

OPEN TYPE: Weight (Kg): 8200 Length L(mm) Width W (mm) Height H (mm):5700x2200x2700 FuelTank Capacity (L): 1600

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.



EAC-1000 DIESEL GENERATOR SET

1)Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.

2)Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

GENERAL SPECIFICATIONS

| Stand By Power: | 1000 kVA – 800 kW |
|-----------------|-------------------|
| Prime Power | 909 kVA – 727 kW |
| Frequency | 50 Hz |
| Cooling System | Water Cooling |

ENGINE

| Engine | CUMMINS |
|-----------------------|--------------------|
| Engine Model | KTA38-G2A |
| Number of Cylinders | 12-V |
| Injection System | Direct |
| Compression Ratio | 14.5 : 1 |
| Bore | 159 mm |
| Stroke | 159 mm |
| Displacement | 38 lt |
| Air Intake | Turbo Aftercooler |
| Speed (RPM) | 1500 rpm |
| Oil Capacity | 135 lt |
| Standby Power | 895 / 1199 kW / hp |
| Prime Power | 813 / 1089 kW / hp |
| Fuel Type | Euro Diesel |
| Governor System | Electronic |
| Cooling System | Water Cooling |
| Coolant Capacity | 350 lt |
| Fuel Consumption Full | 202.3 (lt / hr) |
| Load | |
| Fuel Consumption %75 | 153.7 (lt / hr) |
| Load | |
| Fuel Consumption %50 | 103.1 (lt / hr). |
| Load | |







eagensetenerji