## **ALTERNATOR**

Frequency	50 Hz
Power	200 kVA
Voltage	230 / 400 V
Nb of Phases	3
Aut. Voltage Regulator (AVR)	AS440
Voltage Regulation	±1%
Insulation Class	Н
Protection Standard	IP22-IP23
Power Factor	0.8 Cos

#### **ENGINE**

- CUMMINS heavy duty diesel
- engine 12V / 24V starter and charge
- alternator
  Replaceable air, fuel and oil filters
  Mechanical governor control
  Tropical type radiator
  Flexible fuel hose

- Oil drain valve and extension höse Industrial type silencer and steel compensator Maintenance-free starter battery
- Water jacket heater 1500 rpm engine speed

# **DIMENSIONS & WEIGHT**

WITH CANOPY: Weight (Kg): 1810 Length L(mm) Width W (mm) Height H (mm):3150x1000x1700 FuelTank Capacity (L): 220

OPEN TYPE: Weight (Kg): 1470 Length L(mm) Width W (mm) Height H (mm):2550x1000x1600 FuelTank Capacity (L): 220

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.

## **EAC-200 DIESEL GENERATOR SET**

1)Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't

**2)Prime Power:** The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

# **GENERAL SPECIFICATIONS**

Stand By Power:	200 kVA – 160 kW
Prime Power	182 kVA – 145.4 kW
Frequency	50 Hz
Cooling System	Water Cooling

### **ENGINE**

Engine	CUMMINS
Engine Model	6CTA8.3-G2
Number of Cylinders	6 Inline
Injection System	Direct
Compression Ratio	17.3:1
Bore	114 mm
Stroke	135 mm
Displacement	8.3 lt
Air Intake	Turbo Aftercooler
Speed (RPM)	1500 rpm
Oil Capacity	27.6 lt
Standby Power	180 / 241 kW / hp
Prime Power	163 / 218 kW / hp
Fuel Type	Euro Diesel
Governor System	Electronic
Cooling System	Water Cooling
Coolant Capacity	12.3 lt
Fuel Consumption Full Load	44 (lt / hr)
-	22 (1/1)
Fuel Consumption %75 Load	33 (lt / hr)
Fuel Consumption %50	23 (lt / hr)
Load	







