ALTERNATOR

Frequency	50 Hz
Power	275 kVA
Voltage	230 / 400 V
Nb of Phases	3
Aut. Voltage Regulator (AVR)	AS440
Voltage Regulation	±1%
Insulation Class	Н
Protection Standard	IP22-IP23
Power Factor	0.8 Cos

ENGINE

- CUMMINS heavy duty diesel
- engine 12V / 24V starter and charge
- alternator
 Replaceable air, fuel and oil filters
 Mechanical governor control
 Tropical type radiator
 Flexible fuel hose

- Oil drain valve and extension höse Industrial type silencer and steel compensator Maintenance-free starter battery
- Water jacket heater 1500 rpm engine speed

DIMENSIONS & WEIGHT

WITH CANOPY: Weight (Kg): 2780 Length L(mm) Width W (mm) Height H (mm):3500x1200x1850 Fuel Tank Capacity (L): 360

OPEN TYPE: Weight (Kg): 2440 Length L(mm) Width W (mm) Height H (mm):2900x1200x1750 FuelTank Capacity (L): 360

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.

EAC-275 DIESEL GENERATOR SET

1)Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't

2)Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

GENERAL SPECIFICATIONS

Stand By Power:	275 kVA – 220 kW
Prime Power	250 kVA – 200 kW
Frequency	50 Hz
Cooling System	Water Cooling

ENGINE

Engine	CUMMINS
Engine Model	MTA11-G2
Number of Cylinders	6 Inline
Injection System	Direct
Compression Ratio	16.1:1
Bore	125 mm
Stroke	147 mm
Displacement	11 lt
Air Intake	Turbo Aftercooler
Speed (RPM)	1500 rpm
Oil Capacity	34 lt
Standby Power	246 / 333 kW / hp
Prime Power	224 / 302 kW / hp
Fuel Type	Euro Diesel
Governor System	Electronic
Cooling System	Water Cooling
Coolant Capacity	35 lt
Fuel Consumption Full	50 (lt / hr)
Load	
Fuel Consumption %75	38 (lt / hr)
Load	
Fuel Consumption %50	27.2 (lt / hr)
Load	







