

ALTERNATOR

50 Hz
30 kVA
230 / 400 V
3
AS440
±1%
Н
IP22-IP23
0.8 Cos

ENGINE

- CUMMINS heavy duty diesel
- engine 12V / 24V starter and charge
- 12V / 24V starter and charge alternatör Replaceable air, fuel and oil filters Mechanical governor control Tropical type radiator Flexible fuel höse
- -
- Oil drain valve and extension höse Industrial type silencer and steel compensator Maintenance-free starter battery _

- Water jacket heater 1500 rpm engine speed

DIMENSIONS & WEIGHT

WITH CANOPY: Weight (Kg): 880 Length L(mm) Width W (mm) Height H (mm):2300x950x1400 FuelTank Capacity (L): 140

OPEN TYPE: Weight (Kg): 725 Length L(mm) Width W (mm) Height H (mm):1900x950x1400 FuelTank Capacity (L): 140

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.



EAC-30 DIESEL GENERATOR SET

1)Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.

2)Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

GENERAL SPECIFICATIONS

Stand By Power:	30 kVA - 24 kW
Prime Power	27.2 kVA - 21.8 kW
Frequency	50 Hz
Cooling System	Water Cooling

ENGINE

Engine	CUMMINS
Engine Model	4B3.9-G1
Number of Cylinders	4 Inline
Injection System	Direct
Compression Ratio	17.3 : 1
Bore	102 mm
Stroke	120 mm
Displacement	3.9 lt
Air Intake	Naturally Aspirated
Speed (RPM)	1500 rpm
Oil Capacity	10,9 lt
Standby Power	27 / 36 kW / hp
Prime Power	24 / 32 kW / hp
Fuel Type	Euro Diesel
Governor System	Mechanical
Cooling System	Water Cooling
Coolant Capacity	8.3 lt
Fuel Consumption Full	7.1 (lt / hr)
Load	
Fuel Consumption %75	5.7 (lt / hr)
Load	
Fuel Consumption %50	4.3 (lt / hr)
Load	





eagensetenerji