ALTERNATOR

Frequency	50 Hz
Power	420 kVA
Voltage	230 / 400 V
Nb of Phases	3
Aut. Voltage Regulator (AVR)	AS440
Voltage Regulation	±1%
Insulation Class	Н
Protection Standard	IP22-IP23
Power Factor	0.8 Cos

ENGINE

- CUMMINS heavy duty diesel
- engine 12V / 24V starter and charge
- alternatör alternator Replaceable air, fuel and oil filters Mechanical governor control Tropical type radiator Flexible fuel hose

- _
- Oil drain valve and extension höse Industrial type silencer and steel compensator Maintenance-free starter battery
- Water jacket heater 1500 rpm engine speed

DIMENSIONS & WEIGHT

WITH CANOPY: Weight (Kg): 3765 Length L(mm) Width W (mm) Height H (mm):4000x1500x2200 Fuel Tank Capacity (L): 630

OPEN TYPE: Weight (Kg): 3275 Length L(mm) Width W (mm) Height H (mm):3300x1500x2100 FuelTank Capacity (L): 630

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.



EAC-420 DIESEL GENERATOR SET

1)Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.

2)Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

GENERAL SPECIFICATIONS

Stand By Power:	420 kVA – 336 kW
Prime Power	382 kVA – 306 kW
Frequency	50 Hz
Cooling System	Water Cooling

ENGINE

Engine	CUMMINS
Engine Model	NTAA855-G7
Number of Cylinders	6 Inline
Injection System	Direct
Compression Ratio	14 : 1
Bore	140 mm
Stroke	152 mm
Displacement	14 lt
Air Intake	Turbo Aftercooler
Speed (RPM)	1500 rpm
Oil Capacity	39 lt
Standby Power	377 / 505 kW / hp
Prime Power	343 / 460 kW / hp
Fuel Type	Euro Diesel
Governor System	Electronic
Cooling System	Water Cooling
Coolant Capacity	55 lt
Fuel Consumption Full	89.2 (lt / hr)
Load	
Fuel Consumption %75	67.8 (lt / hr)
Load	
Fuel Consumption %50	47.5 (lt / hr)
Load	





eagensetenerji