

EAGENSET

ALTERNATOR

Frequency	50 Hz
Power	88 kVA
Voltage	230 / 400 V
Nb of Phases	3
Aut. Voltage Regulator (AVR)	AS440
Voltage Regulation	±1%
Insulation Class	H
Protection Standard	IP22-IP23
Power Factor	0.8 Cos

ENGINE

- CUMMINS heavy duty diesel engine
- 12V / 24V starter and charge alternator
- Replaceable air, fuel and oil filters
- Mechanical governor control
- Tropical type radiator
- Flexible fuel hose
- Oil drain valve and extension hose
- Industrial type silencer and steel compensator
- Maintenance-free starter battery
- Water jacket heater
- 1500 rpm engine speed

DIMENSIONS & WEIGHT

WITH CANOPY: Weight (Kg): 1270
Length L(mm) Width W (mm) Height H (mm): 2800x1000x1500 Fuel Tank Capacity (L): 195

OPEN TYPE: Weight (Kg): 1076 Length L(mm) Width W (mm) Height H (mm): 2350x1000x1450 Fuel Tank Capacity (L): 195

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.

EAC-88 DIESEL GENERATOR SET

1) **Standby power:** The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.

2) **Prime Power:** The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

GENERAL SPECIFICATIONS

Stand By Power:	88 kVA – 70.4 kW
Prime Power	80 kVA - 64 kW
Frequency	50 Hz
Cooling System	Water Cooling

ENGINE

Engine	CUMMINS
Engine Model	4BTA3.9-G11
Number of Cylinders	4 Inline
Injection System	Direct
Compression Ratio	17.3 : 1
Bore	102 mm
Stroke	120 mm
Displacement	3.9 lt
Air Intake	Turbo Aftercooler
Speed (RPM)	1500 rpm
Oil Capacity	10,9 lt
Standby Power	80 / 107 kW / hp
Prime Power	70 / 93 kW / hp
Fuel Type	Euro Diesel
Governor System	Electronic
Cooling System	Water Cooling
Coolant Capacity	8.3 lt
Fuel Consumption Full Load	17.6 (lt / hr)
Fuel Consumption %75 Load	13.2 (lt / hr)
Fuel Consumption %50 Load	9.1 (lt / hr)



Info@eagenset.com



[eagensetenerji](https://twitter.com/eagensetenerji)



+905052321982



[eagenset](https://www.linkedin.com/company/eagenset)