

# EAGENSET

## ALTERNATOR SPECIFICATIONS

Alternator brand	Megatron
Type	Brushless, revolving field
Frequency	50 Hz
Winding pitch	2/3 pitch
Number of bearing	Single bearing
Protection	IP23
Insulation system	Class H
Standard temperature rise	Standart 125°C ,Stand by 163°C
Exciter type	Self - excitation or other excitation by PMG
Phase rotation	A (U), B (V), C (W)
Alternator cooling	Direct drive centrifugal blower fan
AC waveform total harmonic distortion (THDV)	No load <1.5%. Non distorting balanced linear load <5%

## DIMENSIONS AND WEIGHTS

Open type: Dry Weight (kg): 2630  
Length(mm) Width (mm) Height (mm):3100x1100x2400 Tank Capacity (L): 240

Canopy type: Dry Weight (kg): 2960  
Length(mm) Width (mm) Height (mm):3450x1300x2550 Tank Capacity (L): 240

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.



[Info@eagenset.com](mailto:Info@eagenset.com)



[eagensetenerji](https://twitter.com/eagensetenerji)



+905052321982



[eagenset](https://www.linkedin.com/company/eagenset)

## EAD-480 DIESEL GENERATOR SET

**Stand by Rating (ESP):** It is the way that generators operate under variable load at certain time intervals. It can work as a backup power. It is not suitable to work under extreme load.

**Prime Rating (PRP):** Applicable for supplying power to varying electrical load for unlimited hours. 10 % overload capability is available for a period of operation

## OUTPUT RATINGS

Genset Model	EAD-480
Engine Model	DDE 11.5 YTO1
Prime rating	363 kVA
Stand by rating	417 kVA
Max. kVA rating	480 kVA

## ENGINE SPECIFICATIONS

Engine brand	Detroit Engine
Aspiration Type	Turbocharged
Engine Rated Speed	1500 rpm
Bore	126 mm
Stroke	130 mm
Displacement	11.54 L
Cylinder block	6 cylinder, vertical
Oil Capacity	24 L
Coolant capacity	23 L
Starting voltage	24 V
Fuel system	Direct injection
Fuel filter	Strata pore fuel filter
Air cleaner type	Heavy duty air cleaner
Compression ratio	16,5:1
Cycle	4 stroke
Cooling system	Water cooled
Governor Type	Electronic
Fuel Consumption 50%	39,7 L/hr
Fuel Consumption 75%	59,5 L/hr
Fuel Consumption 100%	77,3 L/hr