EAGENSET

ALTERNATOR SPECIFICATIONS

Alternator brand	Megatron
Туре	Brushless, revolving field
Frequency	50 Hz
Winding pitch	2/3 pitch
Number of bearing	Single bearing
Protection	IP23
Insulation system	Class H
Standard temperature rise	Standart 125°C ,Stand by 163°C
Exciter type	Self - excitation or other excitation by PMG
Phase rotation	A (U), B (V), C (W)
Alternator cooling	Direct drive centrifugal blower fan
AC waveform total harmonic distortion (THDV)	No load <1.5%. Non distorting balanced linear load <5%

DIMENSIONS AND WEIGHTS

Open type: Dry Weight (kg): 4900 Length(mm) Width (mm) Height (mm): 4600x2000x2700 Tank Capacity (L): 1100

Canopy type: Dry Weight (kg): 5200 Length(mm) Width (mm) Height (mm):4900x2000x3200 Tank Capacity (L): 1100

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.

EAO-1100 DIESEL GENERATOR SET

Stand by Rating (ESP): It is the way that generators operate under variable load at certaintime intervals. It can work as a backup power. It is not suitable to work under extreme load.

Prime Rating (PRP): Applicable for supplying power to varying electrical load for unlimited hours. 10 % overload capability is available for a period of operation

OUTPUT RATINGS

Genset Model	EAO-1100
Engine Model	OPE 29.6K
Prime rating	832 kVA
Stand by rating	957 kVA
Max. kVA rating	1100 kVA

ENGINE SPECIFICATIONS

Optimus Engine
Turbocharged
1500 rpm
138 mm
160 mm
29,6 L
12 cylinder, vertical
60 L
130 L
24 V
Direct injection
Strata pore fuel filter
Heavy duty air cleaner
17:1
4 stroke
Water cooled
Mechanical
111 L/hr
162 L/hr
215 L/hr
245 L/hr







