# EAGENSET

# ALTERNATOR SPECIFICATIONS

| Alternator brand                                      | Megatron  |
|---|---|
| Туре  | Brushless, revolving field                                      |
| Frequency   | 50 Hz   |
| Winding pitch   | 2/3 pitch   |
| Number of bearing                                     | Single bearing  |
| Protection  | IP23  |
| Insulation system                                     | Class H   |
| Standard temperature rise                             | Standart 125°C<br>,Stand by 163°C                               |
| Exciter type  | Self - excitation<br>or other<br>excitation by<br>PMG           |
| Phase rotation  | A (U), B (V), C<br>(W)  |
| Alternator cooling                                    | Direct drive<br>centrifugal<br>blower fan                       |
| AC waveform<br>total harmonic<br>distortion<br>(THDV) | No load <1.5%.<br>Non distorting<br>balanced linear<br>load <5% |

# DIMENSIONS AND WEIGHTS

Open type: Dry Weight (kg): 1480 Length(mm) Width (mm) Height (mm):2500x1000x1650 Tank Capacity (L): 184,8

Canopy type: Dry Weight (kg): 1600 Length(mm) Width (mm) Height (mm):2900x1000x1750 Tank Capacity (L): 184,8

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.

#### **EAO-175 DIESEL GENERATOR SET**

Stand by Rating (ESP): It is the way that generators operate under variable load at certaintime intervals. It can work as a backup power. It is not suitable to work under extreme load.

Prime Rating (PRP): Applicable for supplying power to varying electrical load for unlimited hours. 10 % overload capability is available for a period of operation

## **OUTPUT RATINGS**

| Genset Model    | EAO-175     |
|-----------------|-------------|
| Engine Model    | OPE 7.0 TWE |
| Prime rating    | 132 kVA     |
| Stand by rating | 152 kVA     |
| Max. kVA rating | 175 kVA     |

## **ENGINE SPECIFICATIONS**

| Engine brand          | Optimus Engine          |
|-----------------------|-------------------------|
| Aspiration Type       | Turbocharged            |
| Engine Rated Speed    | 1500 rpm                |
| Bore                  | 105 mm                  |
| Stroke                | 135 mm                  |
| Displacement          | 7.01 L                  |
| Cylinder block        | 6 cylinder, vertical    |
| Oil Capacity          | 15 L                    |
| Coolant capacity      | 25 L                    |
| Starting voltage      | 24 V                    |
| Fuel system           | Direct injection        |
| Fuel filter           | Strata pore fuel filter |
| Air cleaner type      | Heavy duty air cleaner  |
| Compression ratio     | 16:1                    |
| Cycle                 | 4 stroke                |
| Cooling system        | Water cooled            |
| Governor Type         | Mechanical              |
| Fuel Consumption 50%  | 15,9 L/hr               |
| Fuel Consumption 75%  | 24,7 L/hr               |
| Fuel Consumption 100% | 32,5 L/hr               |
| FuelConsumption 110%  | 35,8 L/hr               |







