# EAGENSET

### ALTERNATOR SPECIFICATIONS

Alternator brand	Megatron
Туре	Brushless, revolving field
Frequency	50 Hz
Winding pitch	2/3 pitch
Number of bearing	Single bearing
Protection	IP23
Insulation system	Class H
Standard temperature rise	Standart 125°C ,Stand by 163°C
Exciter type	Self - excitation or other excitation by PMG
Phase rotation	A (U), B (V), C (W)
Alternator cooling	Direct drive centrifugal blower fan
AC waveform total harmonic distortion (THDV)	No load <1.5%. Non distorting balanced linear load <5%

#### DIMENSIONS AND WEIGHTS

Open type: Dry Weight (kg): 1800 Length(mm) Width (mm) Height (mm):2750x1050x1750 Tank Capacity (L): 198

Canopy type: Dry Weight (kg): 2080 Length(mm) Width (mm) Height (mm):3100x1050x2100 Tank Capacity (L): 198

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.



# **EAO-250 DIESEL GENERATOR SET**

Stand by Rating (ESP): It is the way that generators operate under variable load at certaintime intervals. It can work as a backup power. It is not suitable to work under extreme load.

**Prime Rating (PRP):** Applicable for supplying power to varying electrical load for unlimited hours. 10 % overload capability is available for a period of operation

## **OUTPUT RATINGS**

Genset Model	EAO-250
Engine Model	OPE 7.5 TWE-2
Prime rating	189 kVA
Stand by rating	217 kVA
Max. kVA rating	250 kVA

## **ENGINE SPECIFICATIONS**

Engine brandOptimus EngineAspiration TypeTurbochargedEngine Rated Speed1500 rpmBore113 mmStroke130 mmDisplacement7.52 LCylinder block6 cylinder, verticalOil Capacity16 LCoolant capacity25 LStarting voltage24 VFuel systemDirect injectionFuel filterStrata pore fuel filterAir cleaner typeHeavy duty air cleanerCooling system17:1Cycle4 strokeCooling systemWater cooledGovernor TypeMechanicalFuel Consumption 50%35 L/hr		
Engine Rated Speed1500 rpmBore113 mmStroke130 mmDisplacement7.52 LCylinder block6 cylinder, verticalOil Capacity16 LCoolant capacity25 LStarting voltage24 VFuel systemDirect injectionFuel filterStrata pore fuel filterAir cleaner typeHeavy duty air cleanerCooling systemWater cooledGovernor TypeMechanical	Engine brand	Optimus Engine
Bore113 mmStroke130 mmDisplacement7.52 LCylinder block6 cylinder, verticalOil Capacity16 LCoolant capacity25 LStarting voltage24 VFuel systemDirect injectionFuel filterStrata pore fuel filterAir cleaner typeHeavy duty air cleanerCooling systemWater cooledGovernor TypeMechanical	Aspiration Type	Turbocharged
Stroke130 mmDisplacement7.52 LCylinder block6 cylinder, verticalOil Capacity16 LCoolant capacity25 LStarting voltage24 VFuel systemDirect injectionFuel filterStrata pore fuel filterAir cleaner typeHeavy duty air cleanerCompression ratio17:1Cycle4 strokeCooling systemWater cooledGovernor TypeMechanical	Engine Rated Speed	1500 rpm
Displacement7.52 LCylinder block6 cylinder, verticalOil Capacity16 LCoolant capacity25 LStarting voltage24 VFuel systemDirect injectionFuel filterStrata pore fuel filterAir cleaner typeHeavy duty air cleanerCompression ratio17:1Cycle4 strokeCooling systemWater cooledGovernor TypeMechanical	Bore	113 mm
Cylinder block6 cylinder, verticalOil Capacity16 LCoolant capacity25 LStarting voltage24 VFuel systemDirect injectionFuel filterStrata pore fuel filterAir cleaner typeHeavy duty air cleanerCompression ratio17:1Cycle4 strokeCooling systemWater cooledGovernor TypeMechanical	Stroke	130 mm
Oil Capacity16 LCoolant capacity25 LStarting voltage24 VFuel systemDirect injectionFuel filterStrata pore fuel filterAir cleaner typeHeavy duty air cleanerCompression ratio17:1Cycle4 strokeCooling systemWater cooledGovernor TypeMechanical	Displacement	7.52 L
Coolant capacity25 LStarting voltage24 VFuel systemDirect injectionFuel filterStrata pore fuel filterAir cleaner typeHeavy duty air cleanerCompression ratio17:1Cycle4 strokeCooling systemWater cooledGovernor TypeMechanical	Cylinder block	6 cylinder, vertical
Starting voltage24 VFuel systemDirect injectionFuel filterStrata pore fuel filterAir cleaner typeHeavy duty air cleanerCompression ratio17:1Cycle4 strokeCooling systemWater cooledGovernor TypeMechanical	Oil Capacity	16 L
Fuel systemDirect injectionFuel filterStrata pore fuel filterAir cleaner typeHeavy duty air cleanerCompression ratio17:1Cycle4 strokeCooling systemWater cooledGovernor TypeMechanical	Coolant capacity	25 L
Fuel filterStrata pore fuel filterAir cleaner typeHeavy duty air cleanerCompression ratio17:1Cycle4 strokeCooling systemWater cooledGovernor TypeMechanical	Starting voltage	24 V
Air cleaner typeHeavy duty air cleanerCompression ratio17:1Cycle4 strokeCooling systemWater cooledGovernor TypeMechanical	Fuel system	Direct injection
Compression ratio17:1Cycle4 strokeCooling systemWater cooledGovernor TypeMechanical	Fuel filter	Strata pore fuel filter
Cycle4 strokeCooling systemWater cooledGovernor TypeMechanical	Air cleaner type	Heavy duty air cleaner
Cooling system Water cooled   Governor Type Mechanical	Compression ratio	17:1
Governor Type Mechanical	Cycle	4 stroke
	Cooling system	Water cooled
Fuel Consumption 50% 35 L/hr	Governor Type	Mechanical
	Fuel Consumption 50%	35 L/hr
Fuel Consumption 75%41 L/hr	Fuel Consumption 75%	41 L/hr
Fuel Consumption 100%47 L/hr	Fuel Consumption 100%	47 L/hr
FuelConsumption 110%51 L/hr	FuelConsumption 110%	51 L/hr





