EAGENSET

ALTERNATOR SPECIFICATIONS

Alternator brand	Megatron
Туре	Brushless, revolving field
Frequency	50 Hz
Winding pitch	2/3 pitch
Number of bearing	Single bearing
Protection	IP23
Insulation system	Class H
Standard temperature rise	Standart 125°C ,Stand by 163°C
Exciter type	Self - excitation or other excitation by PMG
Phase rotation	A (U), B (V), C (W)
Alternator cooling	Direct drive centrifugal blower fan
AC waveform total harmonic distortion (THDV)	No load <1.5%. Non distorting balanced linear load <5%

DIMENSIONS AND WEIGHTS

Open type: Dry Weight (kg): 2700 Length(mm) Width (mm) Height (mm):3150x1200x2300 Tank Capacity (L): 1100

Canopy type: Dry Weight (kg): 3900 Length(mm) Width (mm) Height (mm):4300x1650x3000 Tank Capacity (L): 1100

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.



EAO-525 DIESEL GENERATOR SET

Stand by Rating (ESP): It is the way that generators operate under variable load at certaintime intervals. It can work as a backup power. It is not suitable to work under extreme load.

Prime Rating (PRP): Applicable for supplying power to varying electrical load for unlimited hours. 10 % overload capability is available for a period of operation

OUTPUT RATINGS

Genset Model	EAO-525
Engine Model	OPE 9.8 TWE-3
Prime rating	397 kVA
Stand by rating	456 kVA
Max. kVA rating	525 kVA

ENGINE SPECIFICATIONS

Optimus Engine
Turbocharged
1500 rpm
135 mm
150 mm
9,8 L
6 cylinder, vertical
33 L
46 L
24 V
Direct injection
Strata pore fuel filter
Heavy duty air cleaner
16:1
4 stroke
Water cooled
Mechanical
45 L/hr
67 L/hr
90 L/hr
99 L/hr





