# EAGENSET

## ALTERNATOR SPECIFICATIONS

Alternator brand	Megatron
Туре	Brushless, revolving field
Frequency	50 Hz
Winding pitch	2/3 pitch
Number of bearing	Single bearing
Protection	IP23
Insulation system	Class H
Standard temperature rise	Standart 125°C ,Stand by 163°C
Exciter type	Self - excitation or other excitation by PMG
Phase rotation	A (U), B (V), C (W)
Alternator cooling	Direct drive centrifugal blower fan
AC waveform total harmonic distortion (THDV)	No load <1.5%. Non distorting balanced linear load <5%

# DIMENSIONS AND WEIGHTS

Open type: Dry Weight (kg): 3500 Length(mm) Width (mm) Height (mm):3150x1200x2300 Tank Capacity (L): 1100

Canopy type: Dry Weight (kg): 3900 Length(mm) Width (mm) Height (mm):4300x1650x3000 Tank Capacity (L): 1100

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.

#### **EAO-575 DIESEL GENERATOR SET**

Stand by Rating (ESP): It is the way that generators operate under variable load at certaintime intervals. It can work as a backup power. It is not suitable to work under extreme load.

Prime Rating (PRP): Applicable for supplying power to varying electrical load for unlimited hours. 10 % overload capability is available for a period of operation

## **OUTPUT RATINGS**

Genset Model	EAO-575
Engine Model	OPE 25.8K4
Prime rating	435 kVA
Stand by rating	500 kVA
Max. kVA rating	575 kVA

## **ENGINE SPECIFICATIONS**

Engine brand	Optimus Engine
Aspiration Type	Turbocharged
Engine Rated Speed	1500 rpm
Bore	135 mm
Stroke	155 mm
Displacement	26,6 L
Cylinder block	12 cylinder, vertical
Oil Capacity	50 L
Coolant capacity	125 L
Starting voltage	24 V
Fuel system	Direct injection
Fuel filter	Strata pore fuel filter
Air cleaner type	Heavy duty air cleaner
Compression ratio	16:1
Cycle	4 stroke
Cooling system	Water cooled
Governor Type	Mechanical
Fuel Consumption 50%	61 L/hr
Fuel Consumption 75%	93 L/hr
Fuel Consumption 100%	125 L/hr
FuelConsumption 110%	145 L/hr







