

ALTERNATOR

| Frequency | 50 Hz |
|---------------------------------|-------------|
| Power | 150 kVA |
| Voltage | 230 / 400 V |
| Nb of Phases | 3 |
| Aut. Voltage Regulator (AVR) | AS440 |
| Voltage Regulation | ±1% |
| Insulation Class | Н |
| Protection Standard | IP22-IP23 |
| Power Factor | 0.8 Cos |
| Protection Standard | IP22-IP23 |

ENGINE

- PERKINS heavy duty diesel
- engine 12V / 24V starter and charge
- alternatör
- alternator Replaceable air, fuel and oil filters Mechanical governor control Tropical type radiator Flexible fuel hose
- -
- _
- Oil drain valve and extension höse Industrial type silencer and steel compensator Maintenance-free starter battery
- Water jacket heater 1500 rpm engine speed

DIMENSIONS & WEIGHT

WITH CANOPY: Length L(nm) Width W (mm) Height H (mm):3150x1000x1700 Weight (Kg): 1890 FuelTank Capacity (L): 220

OPEN TYPE: Length L(mm) Width W (mm) Height H (mm):2350x1000x1600 Weight (Kg): 1650 FuelTank Capacity (L): 220

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.



EAP-150 DIESEL GENERATOR SET

1)Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.

2)Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

GENERAL SPECIFICATIONS

| Stand By Power: | 150 kVA – 120 kW |
|-----------------|------------------|
| Prime Power | 136 kVA - 110 kW |
| Frequency | 50 Hz |
| Cooling System | Water Cooling |

ENGINE

| Engine | PERKINS |
|-----------------------|-----------------------|
| Engine Model | 1106A-70TG1 |
| Number of Cylinders | 6 Inline |
| Injection System | Direct |
| Compression Ratio | 18.2 : 1 |
| Bore | 105 mm |
| Stroke | 135 mm |
| Displacement | 7.01 lt |
| Air Intake | Turbo Intercooler |
| Speed (RPM) | 1500 rpm |
| Oil Capacity | 18 lt |
| Standby Power | 135.8 / 183.5 kW / hp |
| Prime Power | 122.7 / 166 kW / hp |
| Fuel Type | Euro Diesel |
| Governor System | Mechanical |
| Cooling System | Water Cooling |
| Coolant Capacity | 22 lt |
| Fuel Consumption Full | 30.1 (lt / hr) |
| Load | |
| Fuel Consumption %75 | 21.9 (lt / hr) |
| Load | |
| Fuel Consumption %50 | 15.2 (lt / hr) |
| Load | |





eagensetenerji