ALTERNATOR

Frequency	50 Hz
Power	17.7 kVA
Voltage	230 / 400 V
Nb of Phases	3
Aut. Voltage Regulator (AVR)	AS440
Voltage Regulation	±1%
Insulation Class	Н
Protection Standard	IP22-IP23
Power Factor	0.8 Cos

ENGINE

- PERKINS heavy duty diesel
- engine 12V / 24V starter and charge
- alternator
 Replaceable air, fuel and oil filters
 Mechanical governor control
 Tropical type radiator
 Flexible fuel hose

- Oil drain valve and extension höse Industrial type silencer and steel compensator Maintenance-free starter battery
- Water jacket heater 1500 rpm engine speed

DIMENSIONS & WEIGHT

WITH CANOPY: Length L(mm) Width W (mm) Height H (mm):2000x900x1200 Weight (Kg): 675 FuelTank Capacity (L): 115

OPEN TYPE: Length L(mm) Width W (mm) Height H (mm):1650x900x1200 Weight (Kg): 545 FuelTank Capacity (L): 115

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.

EAP-17 DIESEL GENERATOR SET

1)Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't

2)Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

GENERAL SPECIFICATIONS

Stand By Power:	17 kVA – 13.6 kW
Prime Power	15.4 kVA - 12.3 kW
Frequency	50 Hz
Cooling System	Water Cooling

ENGINE

Engine	PERKINS
Engine Model	403A-15G2
Number of Cylinders	3 Inline
Injection System	Indirect
Compression Ratio	22.5:1
Bore	84 mm
Stroke	90 mm
Displacement	1.49 lt
Air Intake	Naturally Aspirated
Speed (RPM)	1500 rpm
Oil Capacity	6 lt
Standby Power	15.4 / 20.6 kW / hp
Prime Power	14 / 18.7 kW / hp
Fuel Type	Euro Diesel
Governor System	Mechanical
Cooling System	Water Cooling
Coolant Capacity	6 lt
Fuel Consumption Full Load	4.3 (lt / hr)
Fuel Consumption %75 Load	3.1 (lt / hr)
Fuel Consumption %50 Load	2.24 (lt / hr)







