

EAGENSET

ALTERNATOR

Frequency	50 Hz
Power	250 kVA
Voltage	400 V
Nb of Phases	3
Aut. Voltage Regulator (AVR)	AS440
Voltage Regulation	±1%
Insulation Class	H
Protection Standard	IP22-IP23
Power Factor	0.8 Cos

ENGINE

- PERKINS heavy duty diesel engine
- 12V / 24V starter and charge alternator
- Replaceable air, fuel and oil filters
- Mechanical governor control
- Tropical type radiator
- Flexible fuel hose
- Oil drain valve and extension hose
- Industrial type silencer and steel compensator
- Maintenance-free starter battery
- Water jacket heater
- 1500 rpm engine speed

DIMENSIONS & WEIGHT

WITH CANOPY: Length L(mm) Width W (mm) Height H (mm):3900x1200x2050
Weight (Kg): 2550 FuelTank Capacity (L): 520

OPEN TYPE: Length L(mm) Width W (mm) Height H (mm):3275x1200x1950
Weight (Kg): 2120 FuelTank Capacity (L): 520

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.

EAP-250 DIESEL GENERATOR SET

1) **Standby power:** The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.

2) **Prime Power:** The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

GENERAL SPECIFICATIONS

Stand By Power:	250 kVA – 200 kW
Prime Power	227 kVA - 182 kW
Frequency	50 Hz
Cooling System	Water Cooling

ENGINE

Engine	PERKINS
Engine Model	1206A- E70TTAG2
Number of Cylinders	6 Inline
Injection System	Direct
Compression Ratio	15:8 : 01
Bore	105 mm
Stroke	135 mm
Displacement	7.01 lt
Air Intake	Turbo Aftercooler
Speed (RPM)	1500 rpm
Oil Capacity	16.5 lt
Standby Power	226 / 303 kW / hp
Prime Power	204 / 273 kW / hp
Fuel Type	Euro Diesel
Governor System	Electronic
Cooling System	Water Cooling
Coolant Capacity	25 lt
Fuel Consumption Full Load	50.6 (lt / hr)
Fuel Consumption %75 Load	37.9 (lt / hr)
Fuel Consumption %50 Load	25.2 (lt / hr)



Info@eagenset.com



[eagensetenerji](https://twitter.com/eagensetenerji)



+905052321982



[eagenset](https://www.linkedin.com/company/eagenset)