

ALTERNATOR

50 Hz
33 kVA
230 / 400 V
3
AS440
±1%
Н
IP22-IP23
0.8 Cos

ENGINE

- PERKINS heavy duty diesel
- engine 12V / 24V starter and charge
- alternatör
- alternator Replaceable air, fuel and oil filters Mechanical governor control Tropical type radiator Flexible fuel hose
- _
- Oil drain valve and extension höse Industrial type silencer and steel compensator Maintenance-free starter battery
- Water jacket heater 1500 rpm engine speed

DIMENSIONS & WEIGHT

WITH CANOPY: Length L(mm) Width W (mm) Height H (mm):2200x900x1350 Weight (Kg): 980 FuelTank Capacity (L): 125

OPEN TYPE: Length L(mm) Width W (mm) Height H (mm):1850x900x1350 Weight (Kg): 825 FuelTank Capacity (L): 125

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.



EAP-33 DIESEL GENERATOR SET

1)Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.

2)Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

GENERAL SPECIFICATIONS

Stand By Power:	33 kVA – 26.4 kW
Prime Power	30 kVA - 24 kW
Frequency	50 Hz
Cooling System	Water Cooling

ENGINE

Engine	PERKINS
Engine Model	1103A-33G
Number of Cylinders	3 Inline
Injection System	Direct
Compression Ratio	19.25 : 1
Bore	105 mm
Stroke	127 mm
Displacement	3.3 lt
Air Intake	Naturally Aspirated
Speed (RPM)	1500 rpm
Oil Capacity	8.3 lt
Standby Power	30.4 / 41 kW / hp
Prime Power	27.7 / 37.3 kW / hp
Fuel Type	Euro Diesel
Governor System	Mechanical
Cooling System	Water Cooling
Coolant Capacity	10.2 lt
Fuel Consumption Full	7.2 (lt / hr)
Load	
Fuel Consumption %75	5.6 (lt / hr)
Load	
Fuel Consumption %50	4 (lt / hr)
Load	





