### **ALTERNATOR**

Frequency	50 Hz
Power	495 kVA
Voltage	400 V
Nb of Phases	3
Aut. Voltage Regulator (AVR)	AS440
Voltage Regulation	±1%
Insulation Class	Н
Protection Standard	IP22-IP23
Power Factor	0.8 Cos

#### **ENGINE**

- PERKINS heavy duty diesel
- engine 12V / 24V starter and charge
- Replaceable air, fuel and oil filters Mechanical governor control
- Tropical type radiator Flexible fuel hose

- Oil drain valve and extension höse Industrial type silencer and steel compensator Maintenance-free starter battery
- Water jacket heater 1500 rpm engine speed

# **DIMENSIONS & WEIGHT**

WITH CANOPY: Length L(mm) Width W (mm) Height H (mm):5000x1600x2600 Weight (Kg): 4600 FuelTank Capacity (L): 1200

OPEN TYPE: Length L(mm) Width W (mm) Height H (mm):4500x1600x2500 Weight (Kg): 3960 FuelTank Capacity (L): 1200

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.

## **EAP-500 DIESEL GENERATOR SET**

1)Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't

**2)Prime Power:** The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

# **GENERAL SPECIFICATIONS**

Stand By Power:	500 kVA – 400 kW
Prime Power	454 kVA - 363 kW
Frequency	50 Hz
Cooling System	Water Cooling

#### **ENGINE**

Engine	PERKINS
Engine Model	2506A- E15TAG1
Number of Cylinders	6 Inline
Injection System	Direct
Compression Ratio	16:01
Bore	137 mm
Stroke	171 mm
Displacement	15,5 lt
Air Intake	Turbo Intercooler
Speed (RPM)	1500 rpm
Oil Capacity	62 lt
Standby Power	434 / 590 kW / hp
Prime Power	395 / 537 kW / hp
Fuel Type	Euro Diesel
Governor System	Electronic
Cooling System	Water Cooling
Coolant Capacity	58 lt
Fuel Consumption Full	95 (lt / hr)
Load	
Fuel Consumption %75 Load	72 (lt / hr)
Fuel Consumption %50 Load	50 (lt / hr)







