ALTERNATOR

Frequency	50 Hz
Power	690 kVA
Voltage	230 / 400 V
Nb of Phases	3
Aut. Voltage Regulator (AVR)	AS440
Voltage Regulation	±1%
Insulation Class	Н
Protection Standard	IP22-IP23
Power Factor	0.8 Cos

ENGINE

- PERKINS heavy duty diesel
- engine 12V / 24V starter and charge
- alternatör
- Replaceable air, fuel and oil filters Mechanical governor control
- Tropical type radiator Flexible fuel hose
- .
- Oil drain valve and extension höse Industrial type silencer and steel compensator Maintenance-free starter battery
- Water jacket heater 1500 rpm engine speed

DIMENSIONS & WEIGHT

WITH CANOPY: Length L(mm) Width W (mm) Height H (mm):5000x1700x2800 Weight (Kg): 5400 FuelTank Capacity (L): 1250

OPEN TYPE: Length L(mm) Width W (mm) Height H (mm):4500x1700x2700 Weight (Kg): 4670 FuelTank Capacity (L): 1250

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.



EAP-725 DIESEL GENERATOR SET

1)Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.

2)Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

GENERAL SPECIFICATIONS

Stand By Power:	725 kVA – 580 kW
Prime Power	660 kVA - 528 kW
Frequency	50 Hz
Cooling System	Water Cooling

ENGINE

Engine	PERKINS
Engine Model	2806A- E18TAG2
Number of Cylinders	6 Inline
Injection System	Direct
Compression Ratio	14.5 : 1
Bore	145 mm
Stroke	183 mm
Displacement	18,1 lt
Air Intake	Turbo Intercooler
Speed (RPM)	1500 rpm
Oil Capacity	62 lt
Standby Power	609 / 817 kW / hp
Prime Power	553 / 741 kW / hp
Fuel Type	Euro Diesel
Governor System	Electronic
Cooling System	Water Cooling
Coolant Capacity	61 lt
Fuel Consumption Full	132 (lt / hr)
Load	
Fuel Consumption %75	97 (lt / hr)
Load	
Fuel Consumption %50	66 (lt / hr)
Load	





