ALTERNATOR

Frequency	50 Hz
Power	93 kVA
Voltage	230 / 400 V
Nb of Phases	3
Aut. Voltage Regulator (AVR)	AS440
Voltage Regulation	±1%
Insulation Class	Н
Protection Standard	IP22-IP23
Power Factor	0.8 Cos

ENGINE

- PERKINS heavy duty diesel
- engine 12V / 24V starter and charge
- Replaceable air, fuel and oil filters Mechanical governor control
- Tropical type radiator Flexible fuel hose

- Oil drain valve and extension höse Industrial type silencer and steel compensator Maintenance-free starter battery
- Water jacket heater 1500 rpm engine speed

DIMENSIONS & WEIGHT

WITH CANOPY: Length L(mm) Width W (mm) Height H (mm):2800x1000x1500 Weight (Kg): 1350 FuelTank Capacity (L): 195

OPEN TYPE: Length L(mm) Width W (mm) Height H (mm):2350x1000x1450 Weight (Kg): 1160 FuelTank Capacity (L): 195

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.

EAP-88 DIESEL GENERATOR SET

1)Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't

2)Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

GENERAL SPECIFICATIONS

Stand By Power:	88 kVA – 70.4 kW
Prime Power	80 kVA - 64 kW
Frequency	50 Hz
Cooling System	Water Cooling

ENGINE

Engine	PERKINS
Engine Model	1104A-44TG2
Number of Cylinders	4 Inline
Injection System	Direct
Compression Ratio	17.25 : 1
Bore	105 mm
Stroke	127 mm
Displacement	4.4 lt
Air Intake	Turbo
Speed (RPM)	1500 rpm
Oil Capacity	8 lt
Standby Power	88 / 120 kW / hp
Prime Power	80 / 110 kW / hp
Fuel Type	Euro Diesel
Governor System	Mechanical
Cooling System	Water Cooling
Coolant Capacity	13 lt
Fuel Consumption Full	18.5 (lt / hr)
Load	
Fuel Consumption %75 Load	14.2 (lt / hr)
Fuel Consumption %50	9.8 (lt / hr)
Load	







