ALTERNATOR

Frequency	50 Hz
Power	891 kVA
Voltage	230 / 400 V
Nb of Phases	3
Aut. Voltage Regulator (AVR)	AS440
Voltage Regulation	±1%
Insulation Class	Н
Protection Standard	IP22-IP23
Power Factor	0.8 Cos

ENGINE

- PERKINS heavy duty diesel
- engine 12V / 24V starter and charge
- alternatör
- alternator Replaceable air, fuel and oil filters Mechanical governor control Tropical type radiator Flexible fuel hose
- .
- Oil drain valve and extension höse Industrial type silencer and steel compensator Maintenance-free starter battery
- Water jacket heater 1500 rpm engine speed

DIMENSIONS & WEIGHT

WITH CANOPY: Length L(mm) Width W (mm) Height H (mm):5500x2000x3000 Weight (Kg): 7300 FuelTank Capacity (L): 1400

OPEN TYPE: Length L(mm) Width W (mm) Height H (mm):5000x2000x2850 Weight (Kg): 6000 FuelTank Capacity (L): 1400

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.



EAP-900 DIESEL GENERATOR SET

1)Standby power: The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage. Overloading isn't permissible.

2)Prime Power: The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

GENERAL SPECIFICATIONS

Stand By Power:	900 kVA – 720 kW
Prime Power	818 kVA - 655 kW
Frequency	50 Hz
Cooling System	Water Cooling

ENGINE

Engine	PERKINS
Engine Model	4006-23TAG3A
Number of Cylinders	6 Inline
Injection System	Direct
Compression Ratio	13.6 : 1
Bore	160 mm
Stroke	190 mm
Displacement	22.9 lt
Air Intake	Turbo Intercooler
Speed (RPM)	1500 rpm
Oil Capacity	114 lt
Standby Power	760 / 1019 kW / hp
Prime Power	679 / 910 kW / hp
Fuel Type	Euro Diesel
Governor System	Electronic
Cooling System	Water Cooling
Coolant Capacity	105 lt
Fuel Consumption Full	172 (lt / hr)
Load	
Fuel Consumption %75	130 (lt / hr)
Load	
Fuel Consumption %50	90 (lt / hr)
Load	



